



# SPECIFICATIONS

## 5000 DRAPER HEADER

---

---

### DRAPER, SIDE

Drive.....	Hydraulic
Draper Width in (mm) .....	41 (1041.4)
Draper Speed ft/min (m/sec) .....	0-750 (3.8)

### DRAPER, CENTER DELIVERY

Drive.....	Mechanical Shaft (Reversible)
Draper Width in (mm) .....	60 (1524)
Draper Speed ft/min (m/sec) .....	0-720 (3.8)

### CENTER FEED AUGER

Drive.....	Mechanical, w/Slip Clutch (Reversible)
Width in (mm) .....	69.5 (1765.3)
Diameter in (mm).....	(12" Dia Tube w/3" Flighting) 18.0 (461)
Float in (mm) .....	5.0 (127)

### DIMENSIONS AND WEIGHT

#### Header Weight (Approx) Less Reel

22 Foot lb (kg) .....	1385 (630)
25 Foot lb (kg) .....	1500 (682)
30 Foot lb (kg) .....	2625 (1193)
36 Foot lb (kg) .....	3100 (1410)
Mounting Kit lb (kg) .....	1700 (773)

#### Reel Weight

##### Metal, 5 Bat

22 Foot lb (kg).....	INA
25 Foot lb (kg).....	400 (182)
30 Foot lb (kg).....	460 (209)
36 Foot lb (kg).....	600 (273)

##### Universal Pickup, U2 Pickup

22 Foot lb (kg).....	INA
25 Foot lb (kg).....	520 (260)
30 Foot lb (kg).....	575 (261)
36 Foot lb (kg).....	800 (364)

##### HCC ML Pickup

22 Foot lb (kg).....	INA
25 Foot lb (kg).....	520 (260)
30 Foot lb (kg).....	575 (261)
36 Foot lb (kg).....	800 (364)

# SPECIFICATIONS

## 5000 DRAPER HEADER

---

---

### DIMENSIONS AND WEIGHT (Cont.)

Overall Width	
22 Foot.....	INA
25 Foot ft (m) .....	26.1 (7.98)
30 Foot ft (m) .....	30.9 (9.53)
36 Foot ft (m) .....	37.2 (11.32)
Width of Cut	
22 Foot ft (m) .....	26.1 (7.98)
25 Foot ft (m) .....	25.2 (7.70)
30 Foot ft (m) .....	30.3 (9.22)
36 Foot ft (m) .....	36.3 (11.05)
Transport Width (includes attaching frame) ft (m) .....	9 (4.29)

### OPTIONAL EQUIPMENT

- Hydraulic Fore/Aft Reel S/N Prior to HK61101
- Electric Fore/Aft Reel S/N HK61101 & Up
- Fixed Gauge Wheels, 16 x 6.50-8
- Spring Loaded Gauge Wheels, 9.5L x15, (30 and 36 ft. only)
- Transportation Kit (36 ft. only)